

# PATENT ABSTRACTS OF JAPAN

(11)Publication number : 07-229215

(43)Date of publication of application : 29.08.1995

(51)Int.Cl.

E04B 2/00  
E04B 1/02  
E04B 2/02  
E04F 21/165

(21)Application number : 06-020659 ✓

(71)Applicant : HIROOKA TOSHISADA  
MATSUFUJI TAISUKE

(22)Date of filing : 17.02.1994


(72)Inventor : HIROOKA TOSHISADA  
MATSUFUJI TAISUKE

## (54) BRICK BLOCK UNIT AND MANUFACTURING THEREFOR

### (57)Abstract:

PURPOSE: To promote construction efficiency by pouring joint mortar for absorbing dimension tolerance in alignment faces of a plurality of bricks, and adjusting the thickness of mortar in accordance with tolerance to integrate into standard external form dimension.

CONSTITUTION: Through-holes 1a and 2a having a circular section passing through up and down are formed in an upper brick 1 and a lower brick 2, and a sheath monolithic plate 6 having an upper sheath plate 4 and a lower sheath plate 5 is placed in the through-holes 1a and 2a. After that, alignment faces of a plurality of bricks are opposed to each other and are inserted in a rigid form having the same inside measurement dimension as external form dimension of a brick block unit 10 to be formed. Force-fit of mortar 3 is made to an alignment face between the upper brick 1 and lower brick 2, and the thickness of the mortar 3 is adjusted in accordance with tolerance. Accordingly, degree of horizontal accuracy of the bricks can easily be ensured.



## LEGAL STATUS

[Date of request for examination] 14.02.2001

[Date of sending the examiner's decision of rejection] 29.11.2002

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision]